

# High Performance Industrial & Maintenance Finishes

**Clear High Gloss**  
#2121

**Tint High Gloss**  
#2121-Color#



## **MONOCHEM 21:** Interior/Exterior “Stick to Anything” Primer (Interior Top Coat)

- 2-Component, 100% solids Epoxy Primer/Finish Coat
- ZERO HAP's, Low VOC, Universally Compliant
- “Stick to Anything” Primer: Adheres to almost all water / solvent / alkyd / unknown based coatings with scuffing rarely required. In addition to non porous surfaces (ex. glazes)
- It can be used as an industrial finish coat for interior applications only.
- Industrial Level Resistance Against: Chemicals, abrasions, staining, hot tires, etc.
- Ideal for horizontal or vertical: Concrete, masonry, prepared metals, drywall, plaster, wood, etc.
- Acceptable for use in USDA inspected facilities
- **Available in 20 industrial colors**

**White Base**  
#4050 Semi-Gloss  
#4150 Low-Gloss  
#3950 Eggshell



## **EPOXYGUARD ENAMEL:** Interior/ Exterior Wall Enamel

- 1-Component, Epoxy fortified Acrylic
- ZERO VOC & HAP's/ Universally Compliant
- Resists: Scuffing, scrubbing, peeling, fading, mold and mildew.
- Antimicrobial properties
- Ideal for vertical: Concrete, masonry, drywall, plaster and wood.
- Acceptable for use in USDA inspected facilities.
- **Available in 20 industrial colors**

**White Base**  
#8950 Semi-Gloss  
#9050 Low-Gloss  
#8850 Eggshell



## **EPOXYGUARD 200:** Interior/Exterior

- 2-Component Epoxy/acrylic
- ZERO HAP's, Low VOC, Universally Compliant
- Industrial Level Resistance Against: Hot tires, UV, abrasion, chemicals, etc.
- Antimicrobial properties
- Ideal for horizontal or vertical: Concrete, masonry, drywall, plaster, wood, prepared metals.
- Acceptable for use in USDA inspected facilities
- **Available in 32 standard colors & 20 industrial colors**

**Clear Base**  
#8900 Semi-Gloss  
#9000 Low-Gloss

**White Base**  
#5455 Semi-Gloss  
#5445 Low-Gloss  
#5430 Eggshell



## **PERMASHIELD 100:** Interior/Exterior

- 1-Component Acrylic-Urethane
- ZERO HAP's, Low VOC, Universally Compliant
- Resists: UV, chemicals, abrasions, hot tires, scrubbing, etc.
- Antimicrobial properties
- Ideal for horizontal or vertical: Concrete, masonry, drywall, plaster, wood, prepared metals, etc.
- Very Easy Maintenance: Just clean the sound coating and reapply.
- Acceptable for use in USDA inspected facilities
- **Available in 32 standard colors & 20 industrial colors**

**Deep Tone Base**  
#5450 Semi-Gloss  
#5460 Low-Gloss

**Clear Topcoat**  
#5350 Gloss  
#5355 Matte



## **PERMASHIELD 200:** Interior/Exterior

- 2-Component Aliphatic Polyurethane
- ZERO HAP's, Low VOC, Universally Compliant
- Top Tier Industrial Level Resistance Against: UV, chemicals, abrasions, staining, flash rusting, hot tires, etc.
- Resists: Oils, battery acid, urine, skydrol, 200+ MEK double rubs, and most forms stains.
- Ideal for horizontal or vertical: Concrete, masonry, metal, drywall, plaster, wood.
- Acceptable for use in USDA inspected facilities.
- Cure time accelerators available
- **Available in 20 industrial colors**

**White Base**  
#5360 Gloss  
#5365 Matte

**Neutral Tint Base**  
#5370 Gloss  
#5375 Matte

**Clear High Gloss**  
#1400

**Tint High Gloss**  
#1400-Color#



## **PERMASHIELD 2000:** Interior/Exterior Quick Drying Polyurea

- 2-Component, 100% solids Polyurea
- ZERO VOC & HAP's/ Universally Compliant
- Quick Drying: Normal Foot Traffic: ~5-6 hours; Vehicular Traffic: ~20-24 hours
- Industrial Level Resistance Against: Chemicals, abrasions, staining, hot tires, etc.
- Ideal for horizontal or vertical: Concrete, masonry, prepared metals, drywall, plaster, wood, etc.
- Acceptable for use in USDA inspected facilities.
- **Available in 20 industrial colors**



- **Commercial**
- **Industrial**
- **Residential**

# High Performance Industrial & Maintenance Finishes



**Monochem 21:** 2-Part, Solvent Free, 100% Solids Epoxy

**Epoxyguard Enamel:** 1-Part, Water Base, Epoxy/Acrylic

**Epoxyguard 200:** 2-Part, Water Base, Epoxy/Acrylic

**Permashield 100:** 1-Part, Water Base, Acrylic/Urethane

**Permashield 200:** 2-Part, Water Base, Aliphatic Polyurethane

**Permashield 2000:** 2-Part, Solvent Free, 100% Solids Fast Cure



Manufacturer of  
U.S. SPECIALTY COATINGS

4661 Alger Street • Los Angeles, CA 90039  
Tel: 818-500-8585 • Fax: 818-502-0818  
www.monopoleinc.com • Email: info@monopoleinc.com

STANDARD COLORS

			
299 WHITE	301 SWISS COFFEE	315 SPRING WHITE	305 NAVAJO WHITE
			
307 LINEN WHITE	309 COTTAGE WHITE	311 OFF WHITE	303 ANTIQUE WHITE
			
319 SILVER WHITE	321 FEATHER	327 SILVER BLUE	329 SKY BLUE
			
333 ROSEMARY	335 LIGHT PEPPER	337 FOREST LIGHT	339 LEMON CREME
			
341 GAROLEN PINE	343 CELERY	345 HAZEL GREEN	347 FIRST LEAF
			
349 DEEP WOOD	351 AUTUMN	353 NATURAL SPICE	355 OYSTER GRAY
			
357 TAN	359 ADOBE	361 BUFF	363 QUIET BLUE
			
365 VINTAGE	367 TERRA COTTA	369 SOFT BLUE	371 MEDIUM GRAY















INDUSTRIAL COLORS

			
171 WHITE	173 BLACK	106 MAHOGANY	153 SONORA TAN
			
114 CARMEL TAN	124 SANDSTONE	117 KHAKI	151 DESERT GOLD
			
104 ADOBE	139 RUSTIC RED	130 MIST GREEN	137 FOREST GREEN
			
161 DESERT GRAY	163 METAL GRAY	164 SMOKE GRAY	141 SAPPHIRE BLUE
			
202 SAFETY GREEN	204 SAFETY RED	206 SAFETY YELLOW	208 SAFETY BLUE






Decorative Flooring Additives

Plastic Chips, Color Micras & Color Quartz Granules

Color Chips - 1" Standard Size

610	621	607	626	744	613	606	721	602	603	604	600	608	620
													

Color Micras - 1/4" Standard Size

M1010 Silver	M1020 Gold	M1030 Midnight	M1040 Amber	M1050 Rum
				

Ask about our Color Quartz Granules



Color samples are affected to some degree by the type of light in which they are viewed (sunlight vs. artificial light) and the age of the color card. Occasionally there may be a slight difference between the actual applied color when compared to the color card. Always conduct a test patch for approval by the owner prior to proceeding to the job.